



V-Photron Technology (Shenzhen) Co. Ltd.


Address: 3/F, No.12 Bldg, Longwangmiao Industry Zone, Baishixia, Fuyong Street, Shenzhen, Guangdong, China

http://www.v-photron.com Email: sales@v-photron.com

Tel: +86-755-61148611-401 Fax: 86-755-61148622

Specifications of LED Energy Saving Light

Item Image	Item Name & No.	Description
	Energy Saving Light VPT-SL001D03W	Work Voltage: AC85-265V (50-60Hz) Power: 3W Luminous Flux: 230lm Colo Temperature: 3000K-7000K LED Qty: 108pcs Emitting Color: White/W. White Size: 40*112mm
	Energy Saving Light VPT-SL001D04W	Work Voltage: AC85-265V (50-60Hz) Power: 4W Luminous Flux: 270lm Colo Temperature: 3000K-7000K LED Qty: 65pcs Emitting Color: White/W. White Size: 430*155mm
	Energy Saving Light VPT-SL001S07W	Input Voltage: 90-245V Power: 7W/9W/11W/13W Luminous Flux: 560lm/700lm/860lm/950lm Colo Temperature: 3000K-7000K LED Specification: 30/5050, 44/5050, 56/5050/64/5050 Power Efficiency: 88%
	Energy Saving Light VPT-SL001S08W	Work Voltage: AC110-220V Power Consumption: 8W Colo Temperature: 3000K-7000K Base Type: E27 LED Type: 5050SMD LED LED Qty: 40pcs Luminous Flux: 550-750lm
	Energy Saving Light VPT-SL001S10W	Work Voltage: AC110-220V Power Consumption: 10W Colo Temperature: 3000K-7000K Base Type: E27 LED Type: 5050SMD LED LED Qty: 60pcs Luminous Flux: 700-900lm
	Energy Saving Light VPT-SL001S10W	Work Voltage: 90-245V Power Consumption: 10W Colo Temperature: 3000K-7000K Length: 560mm LED Type: SMD3528 LED LED Qty: 264pcs Luminous Flux: 2500lm
Item Image	Item Name & No.	Description

	Energy Saving Light VPT-SL002S03W	Input Voltage: 90-245V
		Power: 3W/5W/7W/9W/11W/13W
		Color Temperature: 3000K-7000K
		Length: 133mm/135mm/145mm/163mm/180mm
		LED Specification: 16/5050, 24/5050, 36/5050/, 44/5050
		Flux (lm) : 180lm/350lm/560lm/700lm/860lm/950lm

Features:

1. High Energy-Efficient : only 20% power consumption of halogenlamp and incandescent lamp.
2. Wide voltage design available.
3. Environmental Friendly: no mercury or other harmful materials.
4. No flickering & RF interference, No buzzing noise, instant soft start, and low heat.
5. High shock / vibration resistant.
6. 50000-80000 hours Lifespan.

Note:

1. Customized products are available according to your requirements
2. The items are packed in ordinary way.
3. Period of validity for the quotation: 30days