



V-Photron Technology (Shenzhen) Co. Ltd.


Address: 3/F, No.12 Bldg, Longwangmiao Industry Zone, Baishixia, Fuyong Street, Shenzhen, Guangdong, China

http://www.v-photron.com Email: sales@v-photron.com

Tel: +86-755-61148611-401 Fax: 86-755-61148622

Specifications of LED Flood Light

Item Image	Item Name & No.	Description
	LED Flood Light VPT-FL001H03W	Work Voltage: AC12V Luminous Flux: 420-540lm Ambient Temperature: -20 ~ 50°C Color temperature: 2800K-3600K, 4500K-5500K, 6000K-7000K LED Type: High Power LED Grade of protection: IP65
Item Image	Item Name & No.	Description
	LED Flood Light VPT-FL001H15W	Size: ϕ 180 X 160mm Material: Aluminum Power: 15W Voltage: 220V Color: single color Viewing Angle: 30 Protection class: ip65
Item Image	Item Name & No.	Description
	LED Flood Light VPT-FL001H12W	Size: ϕ 180 X 160mm Material: Aluminum Power: 12w Voltage: 220V Color: RGB Viewing Angle: 30 Protection class: Ip65
Item Image	Item Name & No.	Description
	LED Flood Light VPT-FL002H24W	Size: 330 X 160 X 100mm Material: Aluminum Power: 24W (24 X 1W) Voltage: 220V Color: single color (except green) Operating temperature: -20~+50 degrees Protection class: IP65 Lighting distance : 100-120m
Item Image	Item Name & No.	Description
	LED Flood Light VPT-FL001H20W	Work Voltage: AC85-265 V Power Consumption: 20W Developing: ≥ 70 Ambient Temperature: -20~50°C Color temperature: 2700-4500 LED Type: High Power LED

Item Image	Item Name & No.	Description
	LED Flood Light VPT-FL001H30W	Protection class: IP65
		Work Voltage: AC85-265 V
		Power Consumption: 30W
		Developing: ≥ 70
		Ambient Temperature: $-20 \sim 50^{\circ}\text{C}$
		Color temperature: 2700-4500
		LED Type: High Power LED
		Protection class: IP65

Features:

1. High Energy-Efficient : only 20% power consumption of halogenlamp and incandescent lamp.
2. Wide voltage design available.
3. Environmental Friendly: no mercury or other harmful materials.
4. No flickering & RF interference, No buzzing noise, instant soft start, and low heat.
5. High shock / vibration resistant.
6. 50000-80000 hours Lifespan.

Note:

1. Customized products are available according to your requirements
2. The items are packed in ordinary way.
3. Period of validity for the quotation: 30days