



V-Photron Technology (Shenzhen) Co. Ltd.

Address: 3/F, No.12 Bldg, Longwangmiao Industry Zone, Baishixia, Fuyong Street, Shenzhen, Guangdong, China

http://www.v-photron.com Email: sales@v-photron.com

Tel: +86-755-61148611-401 Fax: 86-755-61148622

Specifications of LED Grille Light

| Item Image | Item Name & No. | Description |
|---|--------------------------------|--|
|  | LED Grille Light VPT-GL001D24W | Work Voltage: AC85-260V |
| | | Power Consumption: 24 ± 5% W |
| | | Luminous Flux: 2340lm |
| | | Ambient Temperature: -20 ~ 50°C |
| | | Color temperature: 2800K-3600K, 4500K-5500K, 6000K-7000K |
| | | LED Type: DIP/SMD |
| | | Qty of LED: 360pcs |
| | | Deminsion: 600*600mm |
| Item Image | Item Name & No. | Description |
|  | LED Grille Light VPT-GL001D45W | Work Voltage: AC85-260V |
| | | Power Consumption: 45 ± 5% W |
| | | Luminous Flux: 4680lm |
| | | Ambient Temperature: -20 ~ 50°C |
| | | Color temperature: 2800K-3600K, 4500K-5500K, 6000K-7000K |
| | | 260.00 mA operating current |
| | | LED Type: DIP/SMD |
| | | Qty of LED: 720pcs |
| Deminsion: 1200*600mm | | |

Features:

1. High Energy-Efficient : only 20% power consumption of halogenlamp and incandescent lamp.
2. Wide voltage design available.
3. Environmental Friendly: no mercury or other harmful materials.
4. No flickering & RF interference, No buzzing noise, instant soft start, and low heat.
5. High shock / vibration resistant.
6. 50000-80000 hours Lifespan.

Note:

1. Customized products are available according to your requirements
2. The items are packed in ordinary way.
3. Period of validity for the quotation: 30days